


**GDI ENGINEERING**



## **51 Unit Fitness Facility**

Residencial

**Springtown, Texas**




- MECHANICAL KEYED NOTES:**
- 1 → OUTDOOR HEAT PUMP CONDENSER HOUSEKEEPING PAD - PROVIDE THE PAD SIZE AS PER THE MANUFACTURER'S REQUIREMENTS.
  - 2 → PROVIDE 7 DAYS 24 HOUR PROGRAMMABLE THERMOSTATS - COMPLY WITH IECC FOR ALL CONTROLS REQUIREMENTS.
  - 3 → LIMIT OF ATTIC.
  - 4 → SEE ATTIC PLAN FOR CONDENSATE DRAIN LINE CONTINUATION.


**GDI ENGINEERING**  
 INNOVATING SOLUTIONS  
**GDI ENGINEERING**  
 3707 Cypress Creek Parkway, Suite 310  
 Houston, TX 77068  
 Office: 346-509-5860  
 www.gdiengdesign.com

A








**1** CONDENSATE DRAIN DETAIL  
SCALE: N.T.S.




**2** DUCT ROOF PENETRATION  
SCALE: N.T.S.




**3** PIPE THRU EXTERIOR WALL  
SCALE: N.T.S.




**5** CONDENSATE SUPPORT & INSTALLATION DETAIL  
SCALE: N.T.S.




**6** RIGID SUPPLY DUCT TAP TO SINGLE AIR DIFFUSER  
SCALE: N.T.S.




**8** OUTDOOR HEAT PUMP INSTALLATION DETAIL  
SCALE: N.T.S.




**7** FLEXIBLE DUCT CONNECTION TO SUPPLY AIR DIFFUSER  
SCALE: N.T.S.



**8** FIRE DAMPER ACCESS DETAIL  
SCALE: N.T.S.



1 GROUNDING DETAIL  
SCALE: NTS



2 ONE LINE DIAGRAM  
SCALE: NTS

CONNECTED LOAD									
Location:		A		B		DEMAND TOTAL			
* LOAD SUMMARY	CL	DF	A	B	A	B			
L Lighting	4.15	1.25	2.55	1.60	5.19				
R Convenience Recept	12.92		7.14	5.78	11.17				
H Heating (Space)	36.00	1.25	18.00	18.00	36.00				
C Cooling		1.00							
A HVAC	48.37	1.00	24.18	24.18	48.37				
P Process		1.00							
O Other Continuous		1.25							
K Kitchen	25.71	13.00	11.90	13.80	16.71				
N Noncontinuous		1.00							
		1.00							
<b>Total</b>	<b>127.15</b>		<b>63.78</b>	<b>63.37</b>	<b>117.43</b>				

Total Demand Load (KVA)	117.43
Total Demand Current (A)	489.31
Min. Feeder Ampacity (A)	587.17


PANEL A													
PANELBOARD DESIGNATION													
SYSTEM VOLTAGE	240/120V, 1φ, 3W												
BUS SIZE	600A												
SYSTEM TYPE	NORMAL												
FEEDER PROT	600A-2P C/B Bus Plug												
CONDUCTOR SIZE	500-kcmil - #3G CU												
CONDUCTOR/PHASE	2												
MAINS	600A MCB												
SCCR	FULLY RATED												
MCB RATING	80%												
GROUND FAULT	NO												
FEEDER LENGTH (FT)	100												
FEEDER V. DROP (%)	0.645												
FAULT CURRENT													
KAIC RATING	18												
ENCLOSURE	TYPE 1												

DESCRIPTION	* WIRE	GRD	CB	KVA	A	B	KVA	CB	WIRE	GRD	DESCRIPTION	*	
1 LIGHTING GYM OPEN SPACE	L 2x 14 AWG	- #14G	15A-1P	1.00	1.55	0.55	15A-1P	2x 14 AWG	- #14G		LIGHTING	L 2	
3 LIGHTING CORRIDOR - BATHROOM	L 2x 14 AWG	- #14G	15A-1P	0.60		1.20	0.60	15A-1P	2x 14 AWG	- #14G	LIGHTING CORRIDOR - BATHROOM	L 4	
5 LIGHTING OUTDOOR	L 2x 14 AWG	- #14G	15A-1P	0.50	1.00		0.50	20A-1P	2x 12 AWG	- #12G	SIGNAGE	L 6	
7 EMERGENCY LIGHTS	L 2x 14 AWG	- #14G	15A-1P	0.20		0.40	0.20	20A-1P	2x 12 AWG	- #12G	FIRE ALARM	L 8	
9 RECEPTACLES TREADMILLS	R 2x 12 AWG	- #12G	20A-1P	1.00	2.00		1.00	20A-1P	2x 12 AWG	- #12G	RECEPTACLES TREADMILLS	R 10	
11 RECEPTACLES TREADMILLS	R 2x 12 AWG	- #12G	20A-1P	1.00		2.26	1.26	20A-1P	2x 12 AWG	- #12G	RECEPTACLES GYM	R 12	
13 RECEPTACLES GYM	R 2x 12 AWG	- #12G	20A-1P	1.26	2.16		0.90	20A-1P	2x 12 AWG	- #12G	RECEPTACLES GYM	R 14	
15 FRIDGE	K 2x 12 AWG	- #12G	20A-1P	0.90		2.16	1.26	20A-1P	2x 12 AWG	- #12G	RECEPTACLES	R 16	
17 RECEPTACLES	R 2x 12 AWG	- #12G	20A-1P	0.72	1.62		0.90	20A-1P	2x 12 AWG	- #12G	RECEPTACLES BATHROOMS GFCI	R 18	
19 RECEPTACLES	R 2x 12 AWG	- #12G	20A-1P	1.08		1.26	0.18	20A-1P	2x 12 AWG	- #12G	RECEPTACLE GFCI	R 20	
21 DRINKING FOUNTAIN	R 2x 12 AWG	- #12G	20A-1P	1.00	1.18		0.18	20A-1P	2x 12 AWG	- #12G	RECEPTACLE OUTDOOR	R 22	
23 DRINKING FOUNTAIN	R 2x 12 AWG	- #12G	20A-1P	1.00		2.00	1.00	20A-1P	2x 12 AWG	- #12G	RECEPTACLE EQUIPMENT	K 24	
25 DRYER	K 3x 10 AWG	- #10G	30A-2P	2.60	5.10		2.50	30A-2P	3x 10 AWG	- #10G	UH-01	A 26	
27 DRYER	K 3x 10 AWG	- #10G	30A-2P	2.60		5.10	2.50	30A-2P	3x 10 AWG	- #10G	UH-01	A 28	
29 SAUNA	K 3x 4 AWG	- #6G	80A-2P	8.30	26.30		18.00	200A-2P	3x 3/0 AWG	- #3G	EW-01	H 30	
31 SAUNA	K 3x 4 AWG	- #6G	80A-2P	8.30		26.30	18.00	200A-2P	3x 3/0 AWG	- #3G	EW-01	H 32	
33 RECEPTACLE EQUIPMENT	K 3x 12 AWG	- #12G	20A-2P	1.00	1.00						SPACE	A 34	
35 RECEPTACLE EQUIPMENT	K 3x 12 AWG	- #12G	20A-2P	1.00		1.91	0.91				SPACE	A 36	
37 HP-01	A 3x 4 AWG	- #10G	50A-2P	3.98	4.90		0.91	15A-2P	3x 14 AWG	- #14G	AHU-01	A 38	
39 HP-01	A 3x 4 AWG	- #10G	50A-2P	3.98		4.90	0.91	15A-2P	3x 14 AWG	- #14G	AHU-02	A 40	
41 HP-02	A 3x 4 AWG	- #10G	50A-2P	3.98	4.90		0.91	15A-2P	3x 14 AWG	- #14G	AHU-03	A 42	
43 HP-02	A 3x 4 AWG	- #10G	50A-2P	3.98		4.90	0.91	15A-2P	3x 14 AWG	- #14G	AHU-03	A 44	
45 HP-03	A 3x 4 AWG	- #10G	50A-2P	3.98	4.90		0.91	15A-2P	3x 14 AWG	- #14G	AHU-04	A 46	
47 HP-03	A 3x 4 AWG	- #10G	50A-2P	3.98		4.90	0.91	15A-2P	3x 14 AWG	- #14G	AHU-04	A 48	
49 HP-04	A 3x 4 AWG	- #10G	50A-2P	3.94	4.85		0.91	15A-2P	3x 14 AWG	- #14G	AHU-04	A 50	
51 HP-04	A 3x 4 AWG	- #10G	50A-2P	3.94		6.08	2.15	25A-2P	3x 10 AWG	- #10G	ERV	A 52	
53 RECEPTACLE OUTDOOR	R 2x 12 AWG	- #12G	20A-1P	0.18	2.33		2.15				SPACE	A 54	
55 SPARE			20A-1P								SPACE	A 56	
57 SPARE			20A-1P								SPACE	A 58	
59 SPARE			20A-1P								SPACE	A 60	
				<b>Total Connected Load</b>									
						<b>63.78</b>		<b>63.37</b>					

3 PANEL BOARD SCHEDULE  
SCALE: NTS






- WATER SUPPLY KEYED NOTES:**
- 1—DCW ENTRY - PROVIDE INSULATION FOR FREEZE PROTECTION.
  - 2—BACKFLOW PREVENTER - WILKINS 375 - 1.5" OR EQUAL.
  - 3—FLOOR MOUNTED ELECTRIC WATER HEATER - INSTALL ON A DRAIN PAN - PROVIDE EXPANSION TANK AS PER SCHEDULE OF EQUIPMENT.
  - 4—DCW & DHW DROP IN WALL TO FIXTURE TERMINAL WITH THERMOSTATIC MIXING VALVE.
  - 5—DCW DROP IN WALL TO FIXTURE.
  - 6—DCW & DHW DROP TO SHOWER TERMINAL WITH PRESSURE / TEMPERATURE ANTI-SCALDING BALANCING VALVE.
  - 7—DCW & DHW DROP IN WALL TO FIXTURE TERMINAL.
  - 8—DCW DRINKING FOUNTAIN CONNECTION WITH BACKFLOW PREVENTER AND VACUUM BREAKER.


  
**GDI ENGINEERING**  
 INNOVATING SOLUTIONS  
**GDI ENGINEERING**  
 3707 Cypress Creek Parkway, Suite 310  
 Houston, TX 77068  
 Office: 346-509-5860  
 www.gdiengdesign.com



**GDI ENGINEERING**  
 INNOVATING SOLUTIONS  
**GDI ENGINEERING**  
 3707 Cypress Creek Parkway, Suite 310  
 Houston, TX 77068  
 Office: 346-509-5860  
 www.gdiengdesign.com



SEWER RISER DIAGRAM - NTS



WATER SUPPLY RISER DIAGRAM - NTS

**WATER MAINS SIZING & WATER LOAD CALCULATION**

FROM IPC - TABLE E 103.3 (2)

FIXTURE	OCCUPANCY	W.S.F.U	QTY.	TOTAL W.S.F.U
WC - FLUSHMETER TANK	PUBLIC	2.0	6	12.0
LAVATORY	PUBLIC	2.0	5	10.0
URINAL - 3/4" VALVE	PUBLIC	5.0	3	15.0
SHOWER	PUBLIC	4.0	4	16.0
CLOTHES WASHER - 8 lb	PUBLIC	3.0	1	3.0
DRINKING FOUNTAIN	-	0.25	2	0.5
MOP SINK	-	3.0	1	3.0
<b>TOTAL = 59.5 WFU</b>				
<b>EQUIVALENT FLOW (IPC TABLE E103.3(3))= 32 GPM</b>				
<b>Ø1-1/2" MAIN CW PIPE WILL OPERATE AT AROUND 6 FT/S</b>				

**SCHEDULE OF PLUMBING PIPES MATERIAL**

PIPING SYSTEM	LOCATION	ACCEPTABLE PIPING MATERIAL
VENT	IN RETURN AIR PLENUM SPACES	≤1-1/2", DMV COPPER OR SCHEDULE 40 GALVANIZED PIPE AND FITTINGS
	IN NON-PLENUM AREAS	ASTM D-1785 PVC SCHEDULE 40, SOLVENT CEMENT TYPE JOINTS
SANITARY WASTE	BELOW AND ABOVE GRADE	ASTM D-1785 PVC SCHEDULE 40, SOLVENT CEMENT TYPE JOINTS
	ABOVE SLAB IN RETURN AIR PLENUM SPACES	ASTM A-74 CAST IRON PIPE, HUBLESS SERVICE WEIGHT
DOMESTIC WATER	-	TYPE L COPPER TUBING WITH WROUGHT COPPER FITTINGS AND 95/5 SOLDER JOINTS. OPTIONAL: CPVC PIPES.

**SCHEDULE No. 1  
SWING TANK SCHEDULE**

TAG	EW-01
MANUFACTURER	BRADFORD WHITE
MODEL	CEHD50(A)36 3"CF
TYPE	ELECTRIC - TANK
HEATER INPUT POWER (KW)	36
ELECTRICAL DATA	240V / 1Ø / 60 Hz
NUMBER OF ELEMENTS	4 / SIMULTANEOUS
NOMINAL TANK CAPACITY (GAL)	50
HEATER RECOVERY @ 90°F RISE (GPH)	164
APPROXIMATE SHIPPING WEIGHT (lbs)	460
HEIGHT x DIAMETER	52" x 24"

- NOTES:  
 1. HEATER SHALL HAVE CSA CERTIFIED AND ASME RATED T&P RELIEF VALVE.  
 2. HEATER SHALL HAVE TWO ANODE RODS FOR PROTECTION.  
 3. HEATER SHALL MEET OR EXCEED THE THERMAL EFFICIENCY AND/OR STANDBY LOSS REQUIREMENTS OF THE US DOE AND CURRENT EDITION OF ASHRAE/JESNA 90.1.  
 4. HEATER SHALL HAVE FACTORY SUPPLIED INSULATION BLANKET.  
 5. PROVIDE EXPANSION TANK AS PER KEYED NOTES.  
 6. PROVIDE BASE PAN AS PER INSTALLATION DETAILS.  
 8. PROVIDE UL LISTED FIELD PHASE CONVERSION KIT FOR POWER SUPPLY IF REQUIRED.

**SCHEDULE No. 2  
EXPANSION TANK SCHEDULE**

TAG	ET-01
MANUFACTURER	AMTROL
MODEL	ST-12C
TOTAL VOLUME (GAL)	6.4
MAX. ACCEPTANCE (GAL)	3.2
SYSTEM CONNECTION	3/4"
MAX. WORKING PRESSURE (PSI)	250
APPROXIMATE SHIPPING WEIGHT (lbs)	42
HEIGHT x DIAMETER	14" x 12"

- NOTES:  
 1. EXPANSION TANK SHOULD BE ASME TESTED & STAMPED.  
 2. BLADDER SHOULD BE ANSI/NSF61 APPROVED.  
 3. ALL INTERNAL PARTS MUST COMPLY WITH FDA APPROVALS.  
 4. TANKS SHALL HAVE FACTORY SUPPLIED INSULATION BLANKET.

**SCHEDULE No. 3  
RE-CIRCULATING PUMP SCHEDULE**


TAG	CP-01
MANUFACTURER	GRUNDFOSS
MODEL	ALPHA2 15-/55
ACTUAL FLOW (GPM)	2.2
ACTUAL HEAD (PSI)	3
TYPE OF CONNECTION	FLANGE
POWER SUPPLY	115V / 1Ø / 60 Hz
MAX AMPS DRAW	0.65 AMPS
APPROXIMATE WEIGHT (lbs)	7.37

- NOTES:  
 1. PUMP SHOULD BE ETL CERTIFIED.  
 2. PUMP SHOULD HAVE AUTO ADAPT FEATURE.  
 3. PUMP SHOULD BE LISTED FOR DOMESTIC HOT WATER USE.  
 4. PROVIDE PUMP WITH LED DISPLAY SHOWING THE ENERGY CONSUMPTION AND FLOW.


**DISINFECTION OF POTABLE WATER SYSTEM**

POTABLE WATER SYSTEM EQUIPMENT AND PIPING SHALL BE PURGED OF DELETERIOUS MATTER AND DISINFECTED PRIOR TO UTILIZATION. THE METHOD TO BE FOLLOWED SHALL BE THAT PRESCRIBED BY THE HEALTH AUTHORITY OR AUTHORITY HAVING JURISDICTION OR IN THE ABSENCE OF A PRESCRIBED METHOD, THE PROCEDURE DESCRIBED IN EITHER AWWA C651 OR AWWA C652 OR AS DESCRIBED AS BELOW. THIS REQUIREMENT SHALL APPLY TO "ON-SITE" OR "IN PLANT" FABRICATION OF A SYSTEM OR TO A MODULAR PORTION OF A SYSTEM.


- THE PIPE SYSTEM SHALL BE FLUSHED WITH CLEAN, POTABLE WATER UNTIL DIRTY WATER DOES NOT APPEAR AT THE POINTS OF OUTLET.
- THE SYSTEM OR PART THEREOF SHALL BE FILLED WITH A WATER/CHLORINE SOLUTION CONTAINING NOT LESS THAN 50 PARTS PER MILLION (50mg/L) OF CHLORINE, AND THE SYSTEM OR PART THEREOF SHALL BE VALVES OFF AND ALLOWED TO STAND FOR 24-HOURS. OR THE SYSTEM OR PART THEREOF SHALL BE FILLED WITH A WATER CHLORINE SOLUTION CONTAINING NOT LESS THAN 200 PARTS PER MILLION (200mg/L) OF CHLORINE AND ALLOWED TO STAND FOR 3-HOURS.
- FOLLOWING THE REQUIRED STANDING TIME, THE SYSTEM SHALL BE FLUSHED WITH CLEAN WATER UNTIL THE CHLORINE IS PURGED FROM THE SYSTEM.
- THE PROCEDURE SHALL BE REPEATED WHERE SHOWN BY A BACTERIOLOGICAL EXAMINATION THAT CONTAMINATION REMAINS PRESENT IN THE SYSTEM.




**1** TRAP PRIMER DETAIL  
SCALE: N.T.S.




**2** FLOOR DRAIN WITH TRAP SEAL PROTECTION  
SCALE: N.T.S.




**3** THERMOSTATIC MIXING VALVE DETAIL  
SCALE: N.T.S.




**4** CONDENSATE DRAIN TERMINATION DETAIL  
SCALE: N.T.S.




**5** TYPICAL WASTE & VENT RISERS  
SCALE: N.T.S.



**6** FLOOR CLEAN-OUT DETAIL  
SCALE: N.T.S.



**7** VENT THRU ROOF DETAIL  
SCALE: N.T.S.



**8** ELECTRIC WATER HEATER DETAIL  
SCALE: N.T.S.